

An aerial photograph of a large industrial facility, likely a water treatment plant. A prominent feature is a large, cylindrical tank on the left side, which is emitting a thick plume of white steam or vapor. To the right of the tank, there is a complex network of metal walkways, ladders, and pipes. The overall scene is industrial and somewhat hazy due to the steam.

# **Decarbonating at the St. Michael Treatment Plant: Effect on Cost, Sludge, and Sedimentation**

**Brad Parker: Rosebud Mining**

**Brent Means: Office of Surface Mining**

**Rich Beam: Pa Bureau of Abandoned Mine Reclamation**

# Presentation Topics


1. Background on Decarbonation
2. St. Michael decarbonation retrofit
3. Calculating CO<sub>2</sub> gas transfer coefficients for decarbonation units
4. Use gas transfer coefficients to predict decarbonation at St. Michael
5. Compare predictions to actual decarbonation performance at St. Michael
6. Decarbonation Cost Savings

# Background on Decarbonation

- Goal of decarbonation is to exsolve dissolved carbon dioxide from water to lessen alkali consumption
- Dissolved  $\text{CO}_{2(\text{aq})}$  species release acidity when pH is increased via alkali addition – leads to increased chemical consumption


# Background on Decarbonation

- The amount of CO<sub>2</sub> acidity released is strongly dependent on the change in pH caused by alkali addition
  - E.g. Consider pH 5.7, Alkalinity 48 mg/L as CaCO<sub>3</sub>, TIC 61 mg/L




# Background on Decarbonation/Aeration

- The process of Decarbonation is conducted before any other treatment process to remove  $\text{CO}_2$  before pH is increased
- Decarbonation is the process of mixing water and air to remove  $\text{CO}_{2(\text{aq})}$
- Two common methods of decarbonation in mine water:
  1. Forcing water through air (e.g. Surface Aerators)
  2. Forcing air through water (e.g. Diffused Aeration)



# Methods of Decarbonation: Surface Aerators



**Aka Mechanical Aeration**

# Methods of Decarbonation: Diffused Aerators



# Background


- Mine Drainage contains elevated concentrations of  $\text{CO}_{2(\text{aq})}$
- Recognized by Kostenbader (1970) and Jagman (1988)
- Pa AML interested in improving decarbonation for new treatment plants
- Rosebud Mining interested in retrofitting St. Michael Treatment Plant for decarbonation
- Formed an evaluation team to study decarbonation options




# 3-Step Methodology.

- Evaluation Team used a 3-Step Methodology to evaluate decarbonation systems:
  1. Field-measure  $\text{CO}_{2(\text{aq})}$  gas transfer coefficients for several operating decarbonation systems
  2. Use the measured gas transfer coefficients to predict the decarbonation performance if the systems were scaled and installed at St. Michael
  3. Compare the predicted results to the actual results after a decarbonation unit is installed at St. Michael to validate our understanding of decarbonation

# Project Location




# St. Michael



89,536 = ppmv


8.95% by v

$\log \text{PCO}_2 = -1.05$  (atm)



180 mg/L


# Surface Water/atm



389 = ppmv

0.038% by v

$\log \text{PCO}_2 = -3.41$  (atm)



0.8 mg/L

How long does it take for the carbonated water to achieve equilibrium with atmospheric conditions?


14° C

14° C

# Step 1: Field-Measure Gas Transfer

$$\Delta\text{CO}_{2(\text{aq})}/\text{time} = -K_{\text{LCO}_2, \mathbf{a}} * (\text{CO}_{2(\text{aq})\text{sat atm}} - \text{CO}_{2(\text{aq})\text{raw}})$$

**a** = surface to volume ratio



# Step 1: Field-Measure Gas Transfer

- Studied two sites that use surface aerators for decarbonation. These sites are configured as Continuous stirred Reactors (CSR) (Pump Water into Air)
- Studied two sites that use a Maelstrom Oxidizer for decarbonation. Plug Flow Reactor (Pump Air into Water)

$$\Delta\text{CO}_{2(\text{aq})}/\text{time} = -K_{\text{LCO}_2,\text{a}} * (\text{CO}_{2(\text{aq})\text{sat atm}} - \text{CO}_{2(\text{aq})\text{water}})$$

# Lancashire: Continuous Stirred Reactor Surface Aerator



# Surface Aerator configured as CSR at Lancashire Treatment Plant



# Surface Aerator configured as CSR at Renton Treatment Plant





# Plug Flow Coarse-bubble Aerator at Trent Site



# Plug Flow Coarse-bubble Aerator at Sykesville







# Step 1: Field-Measure Gas Transfer

$$\Delta\text{CO}_{2(\text{aq})}/\text{time} = -K_{\text{LCO}_2,\text{a}} * (\text{CO}_{2(\text{aq})\text{sat atm}} - \text{CO}_{2(\text{aq})\text{raw}})$$

- Time = Measured using dye and stopwatch
- $\text{CO}_{2(\text{aq})\text{water}}$  = Measured  $\text{CO}_{2(\text{aq})}$  using two methods:
  1. Calculated from pH, temp, and alkalinity
  2. Collected Total Inorganic Carbon (TIC) sample for lab analysis
- $\text{CO}_{2(\text{aq})\text{Sat Atm}}$  = Geochemist Workbench to equilibrate water to atmospheric conditions

Measured the retention time at both Plug Flow Reactor sites  
using dye tracer and stopwatch





# Step #2: Predict Decarbonation at St. Michael

- Pumped Flow ranges 2,000 to 10,000 gpm
- pH = 5.75
- Fe = 120-140 mg/L
- Alkalinity = 48 mg/L as CaCO<sub>3</sub>

## 3 Sources of Acidity:

1. Fe ppt
2. CO<sub>2</sub>
3. Calcite ppt






# Step #2: Predict Decarbonation at St. Michael

- St. Michael uses slaked lime to achieve treatment pH 8.7
- 3 sources responsible for lime consumption during pH increase:
  1. Fe ppt
  2. CO<sub>2</sub> Species
  3. Calcite formation (difficult to predict lime consumption)

- Dissolved-precipitate




- Recarbonation



# Step #2: Predict Decarbonation at St. Michael


	pH	Alk	CO2(aq)	CO2 Acidity @ pH 8.7	Fe Acidity
Raw	5.8	60	194	251	121

**Daily Est. Lime Cost treating 3600  
gpm due to Fe and CO2 acidity**



- Estimate purposefully didn't include cost associated with calcite ppt. Very conservative estimate (on purpose)


# Trent Plug Flow $K_{la}$ applied to St. Michael




- A 2,730 gallon tank is required for a 3,600 gpm flow to provide 45.5 sec of RT

# ► Predicted Daily Lime Costs using Trent $K_{la}$

## No Decarbonation



## Decarbonation



- Estimate a 43% reduction in Lime consumption; Not considering effect of calcite ppt.
- Power requirement of 68 HP, so net predicted daily savings = \$297 treating at 3,600 gpm (not considering any reduction in calcite ppt)


# Step #3: Compare Predicted vs. Actual Savings



- 2 Installed in Aug. 2014, each sized for max flow of 2,500 gpm. Two 60 HP blowers with VFD
- At 3,600 gpm,  $\text{CO}_{2(\text{aq})}$  decreased from 183 to 19 mg/L in 46 secs of RT

# Step #3: Compare Predicted vs. Actual Savings

## Predicted (Trent Kla) vs. Actual



# Step #3: Compare Predicted vs. Actual Savings

	Daily Lime pH 8.7 (tons/day)	Annual Electrical Cost for blower	Annual Lime Cost	Annual Net Savings
<b>Predicted No Decarbonation (Assume No calcite ppt)</b>	<b>5.8</b>	<b>NA</b>	<b>299,866</b>	
<b>Actual No Decarbonation</b>	<b>10.1</b>	<b>NA</b>	<b>\$516,110</b>	
<b>Predicted using Trent KLa</b>	<b>3.3</b>	<b>\$51,231</b>	<b>\$168,852</b>	<b>\$117,621</b>
<b>Actual</b>	<b>3.8</b>	<b>\$44,785</b>	<b>\$194,180</b>	<b>\$277,146</b>

# Unexpected side effect of effective Decarbonation: Sedimentation issues





# St. Michael: Unexpected side effect of effective Decarbonation

	Effluent Total Fe (mg/L)	Polymer	Sludge % Solids (w/w)	Sludge pumping Frequency	Sludge Recycle Ratio (recycled solids/produced solids)
No Decarbonation	< 1.6	No	32.9%	Weekly	251:1
Decarbonation	2- 3*	Yes	9.1%	Daily	60: 1


\*Until a polymer, sludge recirculation rate, and sludge pumping program was instituted to solve the settling issue

- Hypothesized the settling issue was a result of drastic reduction in calcite ppt (sludge glue)


# Pre and Post Decarb Sludge Analysis

Method	Method	Units	Pre Decarb	Post Decarb
CO <sub>2</sub> (as CaCO <sub>3</sub> )	ASTM C 471M	% CaCO <sub>3</sub> Dry	67.7%	23.9%
TIC (as CaCO <sub>3</sub> )	ASTM D 1756	% CaCO <sub>3</sub> Dry	63.8%	17.6%
Neutralization Potential, Dry	PA DEP	% CaCO <sub>3</sub> Dry	73.1%	30.1%

**Before Decarbonation 5/2014**



**After Decarbonation 2/18/2015**



# Conclusions

- Its important to determine the amount of CO<sub>2</sub> species in any mine water (not just “AMD”) if pH adjustment occurs via chemical dose
- Important to evaluate whether the payback exists for decarbonation



- Its important to evaluate the type of decarbonation unit for a site (not all decarbonation units created equal)

