

The Gladden Acid Mine Drainage Treatment Facility and Fishing Run Stream Sealing Project

Katie Wood

April 23, 2024



Leading with Science®

The Gladden AMD Treatment Facility



- South Fayette Conservation Group (SFCG) received a \$13,048,446 AML Economic Revitalization (AML Pilot) Grant from the PA DEP Bureau of Abandoned Mine Reclamation in 2019.
- The Gladden Discharge flows from the abandoned Montour No. 2 underground coal mine operated by the former Pittsburgh Coal Company and abandoned circa 1920
- The discharge dumped on average more than 900 gallons (750 – 1,500 gpm) of iron-laden (90 – 130 mg/liter) water into Millers Run every minute (1.3 million gallons per day)



Outline

- Overview of Gladden Treatment Plant
- Identification of Stream Loss
- Methods of Stream Sealing
- Results
- Conclusion





Gladden Discharge into Millers Run and Millers Run into Chartiers Creek

- Raw Discharge: pH=6, Fe 100 ppm
- Flows: Avg=750 gpm, 1,470 gpm max
- Draining 5,500 acres of Mine Workings
- 1,500 acres of Mine Pool

Treatment Plant Design

- A 2.2 million gallons per day (MGD) treatment plant was designed to treat the existing Gladden discharge.
- The Gladden AMD Treatment Facility is the first facility in PA that was designed from inception to be a Hydrogen Peroxide treatment plant.
- The plant includes two pumping stations to extract the AMD water from the mine pool and bring it to the surface for treatment.
- The treatment includes oxidation using industrial grade (50%) hydrogen peroxide addition, polymer addition to form solid precipitates, solids recirculation for enhanced flocculation, and a clarifier and settling/polishing pond to remove the precipitated metals and solids from the water.
- The treated water is discharged to Millers Run, and the sludge is pumped to a portion of the mine that is not hydrologically connected for disposal.

Completed and
Operating Gladden
AMD Treatment
Facility – March 19,
2021



Final Product – Millers Run Near Cuddy Post Office

Gladden AMD Project - Miller's Run



Before



After



2022




Staff from Tetra Tech and South Fayette Conservation Group at the April 26, 2022 Awards Ceremony

The Gladden AMD Treatment Facility Project was the Recipient of a 2022 Pennsylvania Governor's Award for Environmental Excellence


Fishing Run – The Problem

- Identified areas in Fishing Run and an adjacent unnamed tributary where stream loss was occurring, resulting in the water entering into the mine pool of the Gladden Discharge.
- Additionally identified an area adjacent to Fishing Run where water was cut off from entering into the stream and was percolating into the mine pool.

Fishing Run Contribution to Mine Pool



Stream Flow Loss




Fishing Run – The Solution




- Seal 965 linear feet of an unnamed tributary to Millers Run with polyurethane grout.
- Seal 5,035 linear feet of Fishing Run using Geosynthetic Clay Liner.
- Create a 2,800 linear foot diversion ditch to direct flow into Fishing Run.
- Construction started July 2022 and concluded December 2022.



Sealing Location



Stream Sealing Methods – Polyurethane Grout



Stream Sealing Method – Geosynthetic Clay Liner



Stream Sealing Method – Geosynthetic Clay Liner



Preparing Subgrade



Geosynthetic Clay Liner

Stream Sealing Method – Geosynthetic Clay Liner




Oversized River Rock Bottom



Final Product

Diversion Ditch Method



MAT LINED VEGETATED DIVERSION				
STATION	D (FT)	W (FT)	TW (FT)	MAT TYPE (OR EQUAL)
0+00 TO 8+50	2.0	2.0	8.0	NA Green BioNet SC125BN
8+50 TO 13+00	2.0	5.0	13.0	NA Green BioNet SC125BN
13+00 TO 15+00	2.0	5.0	13.0	NA Green Turf Reinforced Mat SC200
15+00 TO 15+50	2.0	5.0	13.0	NA Green BioNet SC125BN
15+50 TO 26+75	3.0	5.0	17.0	NA Green BioNet SC125BN



Results – Water in The Stream




Results – The Numbers at the Gladden AMD Treatment Plant




Average Rate Pre-Sealing – 1,430GPM
 Average Rate Post-Sealing – 930 GPM

Pump Rate

Start of Sealing



Results – The Numbers




Results – The Numbers



Average Monthly Pre-Sealing – 59,870,523 gal

Average Monthly Post-Sealing – 39,380,330 gal

Gallons Pumped



Conclusion

- Stream Sealing and the Diversion has reduced the amount of water entering into the mine pool and has reduced the amount of water needing treatment at the Gladden AMD Treatment Plant.
- The results to date have demonstrated a reduction of an average over 20,000,000 gallons of mine water pumped per month.
- This reduction in the volume of AMD treated has lowered treatment costs and will also reduce wear on the plant.

Partners



- South Fayette Conservation Group
- John Kosky Contracting
- Sub-Technical
- AMD Industries





Thank You



Katie Wood
Environmental Scientist
Katie.wood@tetratech.com

